



WCM-1

(% RH), (), (/ °C)
TP-1, ()

PWT-11

PWT-11 (LED).
0% 100% RH, -10 80
2% (RH) 1

PWT-GIGA

PWT-GIGA (LED) 100
(10) (10)
10% 95% RH, (RH)
2%

SL-1

SL-1 0,2
10% 30%

WSI-5

WSI-5 : 10% 50%

WCM-1

TANEL ELECTRONICS & IT

, 44-100 GLIWICE, KOPERNIKA 121
tel./fax +48 32 234-96-15, +48 32 238-16-15
E-mail: info@tanel.com.pl, http://www.tanel.com.pl



HIT-3

HIT-3 6% 60%
270 ()

XD-30

XD-30 6% 30%
11

WRD-100

WRD-100 6% 100%
11

WIP-22D

WIP-22D 0,3 1,1 / °C 4% 60%
10

60



, WRD-50 "TERMITE"

WRD-50 6% 50%

, HIT-1

HIT-1 6% 50%

, WTR-1

WTR-1 0,2 8% 50% 35% 75%

PPS-60

ED2030 PPS-60L

IP-65. PPS-60R 2 5



, WIP-21B

WIP-21B 0,5% 8%

, WK-1

WK-1 0 10%



, WIM-90

WIM-90 1% 15% 6% 100% (RH) 30% 90%

HYGROPEN® (« ») HYGROPEN

(L D)

(160 27 15)

, MICROplus

MICROplus 6% 50%

MICROplus ()

, WIP-24

WIP-24 ()

4% 60% 10 60 0,3 1,1 / 3 0%

, WIP-21B

WIP-21B 0,5% 8%

, WK-1

WK-1 0 10%



, WIP-20A

WIP-20A 50 2%

12%

, WM-3

WM-3 6% 30%